



type	valve block size	pump flow [l/min]		power kW		dimensions [mm]							R	dry weight [kg]	capacity [litri]		
		min	max	min	max	A	B	C	D	E	F	G			Lm	Lu	Lt
T2*	1 1/4	52	150	2,9	22,0	1090	830	560	410	910	810	690	G 1"	180	70	150	220
T2	1 1/4	52	216	2,9	22,0	1090	830	560	410	910	810	735	G 1 1/4	180	70	150	220
T3	1 1/2	180	432	9,5	44,1	1240	980	685	535	1060	960	860	G 1 1/2	270	100	300	400
T4	2"	432	600	22,0	58,8	1390	1120	750	600	1310	1210	925	G 2"	360	250	400	650

International Protection rating IP 21

(T2\*) : G overall size with shut-off valve up to l/min 150.

(1) : components on request.

(2) : straight end fitting only for R=1 1/4 and R=1 1/2. For R=2" a plastic cap is supplied.

**For different specifications than the ones shown in this datatsheet please consult GMV**

**POWER UNIT "T 3010 EN"**  
**TANKS T - VALVE 3010**  
**Motors in oil - Threephase 2 poles 50-60Hz**

table : 04.001.ENG rev. : F  
date : 21.06.2016 pg. : 1/1

**GMV**